

# WALL RACK



**19"GERMANY**  
EXPORT RACK

## G1 SERIES



Master Key w/logo



Roller



Mounting Pole



Hinge w/logo



Two Plies Steel



A



B

\* Order No. for Black Color : G1-XXXXXB

## FEATURES

- ✦ **Designed and Manufactured** To comply Standards of ANSI/EIA-310D-1992 (Rev.EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part:2, DIN 41494, 19" Standard.
- ✦ **3-Part Designed** Front Door, Central Part and Back Base.
- ✦ **Manufactured** Made from 1.2mm Electro-Galvanized Steel Sheet and 2.0mm for mounting pole, 100% rust proof.
- ✦ **Mounting Pole** Designed to be L-shape angle with 10x10mm square punching hole to increase strength and flexible to adjust freely with screened Rack unit (U) on the mounting pole.
- ✦ **Front Door**
  - For G1-XXXXX model was the steel frame with acrylic 5.0mm thickness and 38 cm width, with film protection (About the height will follow as the size of Rack unit). Door edge with 3-fin type of dust proof rubber seal (Gray color). Support security lock with 19" Germany master key, and trademark embossing on the top.
  - For G1-XXXXXP model was the steel with perforated capsule ventilation surrounding for 50% of door's area.
- ✦ **Central Part** There is sliding rail to adjust the mounting pole. The bottom equipped with special rollers for opening and locking to back base part. The top has pre-punch fan pattern for mounting the fan sets (1-3 fan sets for installation). The both side have ventilation grill and support security locking system with 19" Germany master key same as the front door.
- ✦ **Back Base** There is the clip with 10x10mm for cable access at the top and bottom and can be mounting to the wall with screws by 2.4mm thickness two plies steel on the rear part.
- ✦ **Hinge** Made from 3 pieces of special high strength PVC (ABS) or other materials (as requested), without disturbance noise and rust-free. The front and rear door can reverse to change the opening direction from the left or right side by adjusting screw at the nut of hinge.
- ✦ **Grounding System** 2.5mm copper wire with yellow and green color stripe which connect between cabinet's structure and door.
- ✦ **New Shine Light Gray** Two-tone color painted by Electrostatic powder coating process for scratch resistance.
- ✦ **Screw Set** Provided screws, captive nuts, plastic washer with nickel plating and M6 standard.
- ✦ **Manufacturer and Distributor** Certified by ISO 9001:2015.

## Options

|           |   |                                |
|-----------|---|--------------------------------|
| Color     | : | *Black or other (as requested) |
| Thickness | : | 1.6mm or other (as requested)  |
| Pole      | : | 4 Poles                        |

## Deliverly with

- 3 Master key with key number and trademark embossing
- 4 Sets of wall mounting screw.
- Nut and screw sets according to no. of Rack unit (U).

## ORDERING INFORMATION W=Width 600 mm. Standard

| 1U<br>= 44.45 mm. | Overall<br>Height (mm.) | Order No. of Different Depth (mm.) |           |           | Figure |
|-------------------|-------------------------|------------------------------------|-----------|-----------|--------|
|                   |                         | D = 400                            | D = 500   | D = 600   |        |
| 6U                | 320                     | G1-60406                           | G1-60506  | G1-60606  | A      |
| 9U                | 455                     | G1-60409                           | G1-60509  | G1-60609  |        |
| 12U               | 590                     | G1-60412                           | G1-60512  | G1-60612  |        |
| 6U                | 320                     | G1-60406P                          | G1-60506P | G1-60606P | B      |
| 9U                | 455                     | G1-60409P                          | G1-60509P | G1-60609P |        |
| 12U               | 590                     | G1-60412P                          | G1-60512P | G1-60612P |        |

Sample : G1-60609B Wall Rack 9U, 60 x 60 cm., Black Color

# WALL RACK



**19"GERMANY**  
EXPORT RACK

## G2 SERIES



Master Key w/logo



Roller



Mounting Pole



Hinge w/logo



Two Plies Steel



\* Order No. for Black Color : G2-XXXXXB

## FEATURES

- ❖ **Designed and Manufactured** To comply Standards of ANSI/EIA-310D-1992 (Rev.EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part:2, DIN 41494, 19" Standard.
- ❖ **3-Part Designed** Front Door, Center Part and Back Base.
- ❖ **Manufactured** Made from 1.2mm Electro-Galvanized Steel Sheet and 2.0mm for mounting pole, 100% rust proof.
- ❖ **Mounting Pole** Designed to be L-shape angle with 10x10mm square punching hole to increase strength and flexible to adjust freely with screened Rack unit (U) on the mounting pole.
- ❖ **Front Door** It was the steel frame with acrylic 5.0mm thickness and 38cm width, with film protection (About the height will follow as the size of Rack unit) and perforated capsule surrounding for ventilation. Door edge with 3-fin type of dust proof rubber seal (Gray color). Support security lock with 19" Germany master key, and trademark embossing on the top.
- ❖ **Center Part** There is sliding rail to adjust the mounting pole. The bottom equipped with special rollers for opening and locking to back base part. The top has pre-punch fan pattern for mounting the fan sets (1-3 fan sets for installation). The both side have ventilation grill and support security locking system with 19" Germany master key same as the front door.
- ❖ **Back Base** There is the clip with 10 x 10mm for cable access at the top and bottom and can be mounting to the wall with screws by 2.4mm thickness two plies steel on the rear part.
- ❖ **Hinge** Made from 3 pieces of special high strength PVC (ABS) or other materials (as requested), without disturbance noise and rust-free. The front and rear door can reverse to change the opening direction from the left or right side by adjusting screw at the nut of hinge.
- ❖ **Grounding System** 2.5mm copper wire with yellow and green color stripe which connect between cabinet's structure and door.
- ❖ **New Shine Light Gray** Two-tone color painted by Electrostatic powder coating process for scratch resistance.
- ❖ **Screw Set** Provided screws, captive nuts, plastic washer with nickel plating and M6 standard.
- ❖ **Manufacturer and Distributor** Certified by ISO 9001:2015.

## Options

|           |   |                                      |
|-----------|---|--------------------------------------|
| Color     | : | *Black color or other (as requested) |
| Thickness | : | 1.6mm or other (as requested)        |
| Pole      | : | 4 Poles                              |

## Deliverly with

- 3 Master key with key number and trademark embossing
- 4 Sets of wall mounting screw.
- Nut and screw sets according to no. of Rack unit (U).

## ORDERING INFORMATION W=Width 600 mm. Standard

| 1U<br>= 44.45 mm. | Overall<br>Height (mm.) | Order No. of Different Depth (mm.) |          |          |
|-------------------|-------------------------|------------------------------------|----------|----------|
|                   |                         | D = 400                            | D = 500  | D = 600  |
| 6U                | 320                     | G2-60406                           | G2-60506 | G2-60606 |
| 9U                | 455                     | G2-60409                           | G2-60509 | G2-60609 |
| 12U               | 590                     | G2-60412                           | G2-60512 | G2-60612 |

Sample : G2-60609B Wall Rack 9U, 60 x 60 cm., Black Color